

Copyright 2014 MKKB Enterprises, INC









General Supply List:

Rotary Cutter, Mat, Ruler Scissors Shears and Thread Snips Iron and ironing surface Fabric Marker of your choice (pen, pencil, chalk...) Microtex size 80 or 90 needle or your favorite needle. Machine Feet: Stitch in the ditch foot, 1/4" foot Construction Thread Decorative Thread General Sewing Supplies

Supply List for Stitch and Flip Hot Pad:

Project Supplies:

One 8" square of base fabric Five 2" x 8" strips of fabric Two 9" squares of Insul-Bright (by the Warm Company) One 9" square of fabric for the back of the coaster Binding: 2 1/2" x width of the fabric Bobbin wound with embroidery thread to match the top thread School Glue







NOTE: These directions are to be used in conjunction with the videos.

Instructions:

Gather all the supplies listed on the previous page.

Place the first 2" strip of fabric Right Side Up (RSU) on the 8" square of base fabric lining up the left edge of strip and the square.

Place the second strip of fabric on top of the first strip Right Sides Together (RST) Stitch along the right edge of the the strips using a 1/4" foot to create a 1/4" seam. Flip the second strip so it is RSU and press Place the third strip of fabric on top of the second strip RST Stitch along the right edge of the strips using a 1/4" foot to create a 1/4" seam. Flip the third stip so it is RSU and press Repeat for strips 4 and 5.

Layer:

Hot pad back Wrong Side Up (WSU).

Insul-bright reflective side touching the wrong side of the hot pad back fabric. Insul-bright reflective side up.

Hot pad front wrong side touching the reflective side of the insul-bright

and the right side of the front of the hot pad facing up.

If desired stitch in the ditch through all layers of the pieced hot pad.

Zig Zag around all sides of the hot pad/pot holder keeping the zig zag entirely on the front of the hot pad/pot holder. This will hold all the layers together and make attaching the binding much easier.

Cut away all the excess insul-bright and the hot pad/pot holder back fabric just outside of the zig zag stitch.







Make sure you have cut your biding 2 1/2" wide by the width of the fabric. Press in half lengthwise keeping the raw edges even.

Stitch binding to the front using a 3/8" seam allowance and creating mitered corners

as you go. Please refer to the video to see how this is done.

Iron and glue binding to the back of the hot pad/pot holder.

Thread the sewing machine with decorative thread in the top and the bobbin.

Choose a decorative stitch and stitch the binding in place.

I choose the feather stitch 3.5w and 9.0 L $\,$









MKKB Enterprises, INC www.MargaretMoorehead.com Office: 618-467-0484 Cell: 618-444-2385 Margaret@MargaretMoorehead.com

