

Margaret Moorehead Presents...

Wind Beneath My Wings





Basic Supplies

Sewing/Embroidery Machine Minimum hoop size of 140mm x 225mm Software and Transfer device to load designs Rotary Cutter, Mat, Ruler Scissors

Shears
Thread snips
Iron and ironing surface
Press Cloth
Fabric Marker of your choice (pen, pencil, chalk...)
General Sewing Supplies



Microtex size 80 or 90 needle or your favorite needle for embroidery Machine Feet (These are recommended but not required)

Stitch in the ditch foot (narrow edge stitch foot)

Stabilizers:

Tear Away

Embroidery Thread

Construction Thread

Bobbins (wound with light weight bobbin thread, I use pre-wounds) and bobbins with construction thread Embroidery Design "Wind Beneath My Wings" by Margaret Moorehead Project Fabric and Batting


- A. Frame Fabric: 18" x 12" fused with light weight knit interfacing
- B. Batting Base for project: 18" x 12" fusible batting
- C. Pillow Backing Fabric: Two 12" squares of fabric fused with light weight knit interfacing
- D. Fabric for design in Center of Project: 10" x 6" rectangle fused with light weight knit interfacing
- E. Heart Appliqué' Fabric: 5" square fused with light weight knit interfacing




Preparation

Fuse the light weight interfacing to the back of all your fabrics.


Mark horizontal and vertical center of "B" (18" x 12" fusible batting) and "D" 6' x 12" design fabric Place "D" on top of "B" lining up your marks and fuse together





Embroidery

Use tear away stabilizer
Thread with embroidery thread to stitch out the word part of the design
Center your project under the needle, baste in place and stitch out the word portion of your design






Embroidery Continued


Appliqué Heart stitches next

The first thing to stitch is the outline of the heart that shows exactly where to place your appliqué fabric. Stitch this out and then place your appliqué fabric so it completely covers all those stitches

Note: Be sure your appliqué fabric is fused with light weight interfacing.

Place your appliqué fabric over the heart outline. The next thing to stitch is the outline again to hold the appliqué fabric in place.






Remove the hoop from the machine, but not the project from the hoop and trim away the excess appliqué fabric from around the outside edge of the heart.

Place the hoop back on the machine and continue stitching until the heart embroidery is completed.









Embroidery Continued


Place the "frame fabric" on top of your project lining up the edges of the frame fabric with the edges of the batting.

Note: Be sure the back of your frame fabric is fused with light weight interfacing.

The outline of the frame will be stitched

Remove the hoop from the machine and trim away the fabric from INSIDE the frame





Place the hoop back on the machine and continue stitching until the frame embroidery is completed.





Remove the Basting stitch, and stabilizer. Trim all your threads



Finishing your pillow

Fuse the frame fabric to the batting
Turn under one raw edge of one of the 12" square backing pieces 1/2"
Fold this edge under again to create a nice finished edge.
Stitch this edge in place
Repeat for the other 12" square of backing fabric.

Trim the cushion to 16" wide.

Note: To do this measure out from the center 8" to each side.

Place the backing pieces on top of the embroidered pillow top, right sides together with the stitched down finished edges creating an overlap in the center of the cushion, and the raw edges of the back even with the raw edges of the cushion front. You should have about a 3 1/2" overlap

Note: You may need to trim the back pieces if they are a bit larger then the front cushion from top to bottom. You want the edges on all 4 sides to line up nice and neat.





Stitch all 4 sides using a 1/2" seam allowance. Turn Right sides out Edge stitch if desired





Enjoy!